





www.toptek-hw.com

LED SPACER SUPPORT LEDS-0.8



FOR:LEDS-0.8~LEDS-3.5



MATERIAL 1 : NYLON 66(UL)
FLAME CLASS 1 : 94V-0,94V-2
COLOR 1 : BLACK,NATURAL
UNIT : mm

Application : To protect $\phi 3\text{mm}$ LED and stand up on board with same height, but avoid pins bended, broken, and short-circuit, no fixture necessary, all sizes you need.

PART NO	A	L	P	PACKAGE
LEDS-1	1.0	3.0	1	2000
LEDS-0.8	0.8	3.0	1	2000
LEDS-1.5	1.5	3.0	1	2000
LEDS-2	2.0	3.0	1	2000
LEDS-2.5	2.5	3.0	1	2000
LEDS-3	3.0	3.0	1	2000
LEDS-3.5	3.5	3.0	1	2000
LEDS-4	4.0	3.0	1	2000
LEDS-4.5	4.5	3.0	1	2000
LEDS-5	5.0	3.0	1	1000
LEDS-5.5	5.5	3.0	1	2000
LEDS-6	6.0	3.0	1	2000
LEDS-6.5	6.5	3.0	1	2000
LEDS-7	7.0	3.0	1	2000
LEDS-7.5	7.5	3.0	1	2000

LEDS-8	8.0	3.0	1	2000
LEDS-8.5	8.5	3.0	1	2000
LEDS-9	9.0	3.0	1	2000
LEDS-9.5	9.5	3.0	1	2000
LEDS-9.8	9.8	3.0	1	2000
LEDS-10	10.0	3.0	1	2000
LEDS-10.5	10.5	3.0	1	2000
LEDS-11	11.0	3.0	1	2000
LEDS-11.5	11.5	3.0	1	2000
LEDS-12	12.0	3.0	1	2000
LEDS-12.5	12.5	3.0	1	2000
LEDS-13	13.0	3.0	1	2000
LEDS-13.5	13.5	3.0	1	2000
LEDS-14	14.0	3.0	1	2000
LEDS-14.5	14.5	3.0	1	2000
LEDS-15	15.0	3.0	1	2000
LEDS-15.5	15.5	3.0	1	2000
LEDS-16	16.0	3.0	1	2000
LEDS-16.5	16.5	3.0	1	1000
LEDS-17	17.0	3.0	1	1000
LEDS-17.5	17.5	3.0	1	1000
LEDS-18	18.0	3.0	1	1000
LEDS-18.5	18.5	3.0	1	1000
LEDS-19	19.0	3.0	1	1000
LEDS-19.5	19.5	3.0	1	1000
LEDS-20	20.0	3.0	1	1000
LEDS-20.5	20.5	3.0	1	1000
LEDS-21	21.0	3.0	1	1000
LEDS-21.5	21.5	3.0	1	1000
LEDS-22	22.0	3.0	1	1000
LEDS-22.5	22.5	3.0	1	1000
LEDS-23	23.0	3.0	1	1000
LEDS-23.5	23.5	3.0	1	1000
LEDS-24	24.0	3.0	1	1000